

SYNOX GEAR ATF DEX VI

GEAR ATF DEX VI is a high-quality automatic transmission fluid meeting the requirements of the Dexron VI specification. It has been specifically developed for modern automatic transmissions and provides excellent performance in terms of shift comfort, wear protection, and ageing stability.

The formulation is based on high-quality base oils combined with advanced additive technology, ensuring excellent oxidation stability, high thermal resistance, and stable friction characteristics. This guarantees smooth and precise shifting even under demanding operating conditions.

GEAR ATF DEX VI provides reliable protection against wear, corrosion, and foaming, contributing to extended transmission service life.

APPLICATIONS

- Modern automatic transmissions (step-type AT)
- Power steering systems and hydraulic systems, where approved
- Applications requiring Dexron VI or compatible specifications

APPLICATION RECOMMENDATION

- | | | |
|--------------------------------|--------------------------------|------------------------------------|
| • DEXRON VI | • FORD/LINCOLN/MERCURY P/N | LR0022460 |
| • DEXRON III-H | XT-10-QLV | • MASERATI P/N 231603 |
| • AISIN WARNER AW-1 | • FORD/LINCOLN/MERCURY P/N | • MAZDA FW 6A EL, FW 6AX EL |
| • AISIN WARNER F8FXX | XT-6-QSP OR -DSP [SP] | • MAZDA FZ MERCON LV |
| • AISIN WARNER JWS 3324 | • GM/GMC/OPEL/SATURN AW1 | • MITSUBISHI ATF-J3 |
| • BENTLEY P/N PY112995PA | • GM/GMC/OPEL/SATURN P/N | • MITSUBISHI SP-IV |
| • BMW/MINI P/N 83 22 0 142 516 | 88863400, 88863401 | • NISSAN/INFINITY MATIC-S |
| • BMW/MINI P/N 83 22 0 397 114 | • HONDA/ACURA DW-1 | • PORSCHE P/N 000 043 304 00 |
| • BMW/MINI P/N 83 22 2 163 514 | • HONDA 082000-9017 (ATF TYPE | • SAAB P/N 93 165 147 -AW-1 |
| (BMW 8072 B) | 3.1) | • SHELL 3353 |
| • CHRYSLER/DODGE/JEEP P/N | • HYUNDAI/KIA NWS-9638 T-5 | • SHELL 134 |
| 05127382AA | • HYUNDAI/KIA P/N 040000C90SG | • SHELL 1375.4 |
| • CHRYSLER/DODGE/JEEP P/N | • HYUNDAI/KIA SP-IV / SPH-IV | • TOYOTA/LEXUS/SCION WS |
| 68043742AA | • JAGUAR FLUID 8432 JASO M315, | • VW/AUDI G 052 533, G 055 005, ZF |
| • DAIMLER/MERCEDES MB 236.12, | CLASS 1 | LIFEGUARD 5/6 |
| 236.14, 236.41 | • LAND ROVER P/N TYK500050, | |

Also suitable for applications from:

BMW / Mini, Chrysler / Dodge / Jeep, Jaguar, Land Rover, Mazda, Mitsubishi, Porsche, Saab, Bentley, and other international manufacturers.

For further application, recommendation and specification, please contact our technical sales team.

TYPICAL CHARACTERISTICS

Property	Test Method	Unit	Value
Color	--	–	Red
Density at 15°C	DIN 51757	kg/m ³	841
Viscosity at 40°C	DIN 51562-1	mm ² /s	29,1
Kinematic Viscosity at 100°C	DIN 51562-1	mm ² /s	6,0
Viscosity Index	DIN ISO 2909	°C	161
Pour Point	DIN ISO 3016	°C	-48
Flash Point (COC)	DIN ISO 2592	°C	218

STORAGE AND SHELF LIFE

When stored properly, the product has a shelf life of up to 3 years from the date of manufacture. It should be stored in a dry place and protected from direct sunlight, moisture, and high temperatures.

NOTICE

The values shown represent typical product characteristics and may vary within normal production tolerances.

Always follow the vehicle manufacturer's operating and service recommendations. The information contained in this technical data sheet is based on our current knowledge and experience. However, it does not constitute a legally binding guarantee of specific product properties, as the conditions of application are beyond our control.

We reserve the right to make changes that serve technical improvement or product development.