

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 1 of 11

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

SYNOX GEAR ATF DEX VI

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automatic gear oil

Uses advised against

--

1.3. Details of the supplier of the safety data sheet

Company name:	MIDCO Lubes GmbH
Street:	Bruchkampweg 23
Place:	D-29227 Celle
Telephone:	+49 5141 9880-20
E-Mail:	info@midco-lubes.com
Internet:	www.synox-oil.com

1.4. Emergency telephone number: CHEMTREC: +1-703-527-3887 (international, 24h aday / 7 days a week)
Germany: +49 69 643508409 / Toll free: 0800 1817059

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Regulation (EC) No 1272/2008

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

Additional advice on labelling

The product does not require a hazard warning label in accordance with Regulation (EC) No 1272/2008.

2.3. Other hazards

Product can form a film on the water surface that can prevent oxygen exchange. Refer to section 11, 12 and 15

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 2 of 11

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil - unspecified			45 - < 50 %
	265-090-8	649-454-00-7	01-2119488706-23	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			25 - < 30 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified			10 - < 15 %
	276-738-4	649-483-00-5	01-2119474889-13	
	Asp. Tox. 1; H304			
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified			1 - < 5 %
	276-737-9	649-482-00-X	01-2119474878-16	
	Asp. Tox. 1; H304			
18760-44-6	Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich			1 - < 5 %
	800-172-4		01-2119969520-35	
	Aquatic Chronic 2; H411			

Full text of H and EUH statements: see section 16.

Further Information

The mineral oils in the product contain less than 3 % DMSO extract (IP 346).

Mixtures are not subject to registration. The registration numbers of the ingredients in this mixture (if present) have been listed in item 3.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

Get medical advice/attention if you feel unwell.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.

After contact with skin, wash immediately with plenty of water and soap.

In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Call a

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 3 of 11

physician immediately.

After ingestion

Do NOT induce vomiting. Call a physician immediately.

Observe risk of aspiration if vomiting occurs.

4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date.

4.3. Indication of any immediate medical attention and special treatment needed

First aider: Pay attention to self-protection!

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media****Suitable extinguishing media**

Foam, Carbon dioxide (CO₂), Extinguishing powder, Water spray jet.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

The formation of combustible vapours is possible at temperatures above: Flash point.

In case of fire may be liberated:

Hydrocarbons, Pyrolysis products, toxic, Carbon dioxide (CO₂), Carbon monoxide, Hydrogen sulphide (H₂S),

Nitrogen oxides (NO_x), Phosphorus oxides.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear full chemical protective clothing.

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Additional information

B (Fires of liquids or liquid turning substances)

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation. Special danger of slipping by leaking/spilling product. Conditions to avoid:

Inhalation. Keep away from sources of ignition - No smoking. Avoid contact with eyes and skin.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 4 of 11

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling****Advice on safe handling**

All work processes must always be designed so that the following is excluded: Generation/formation of mist. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle and open container with care.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. Do not put any product-impregnated cleaning rags into your trouser pockets. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.

When using do not eat, drink or smoke. Separate storage of work clothes.

Further information on handling

The formation of combustible vapours is possible at temperatures above: Flash point

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep/Store only in original container.

Hints on joint storage

Keep away from: Oxidising agent, strong

Further information on storage conditions

Do not expose to temperatures above 50 °C.

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

see product information

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 5 of 11

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m³
Worker DNEL, long-term		inhalation	local	5,58 mg/m³
Worker DNEL, long-term		dermal	systemic	0,970 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m³
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2,7 mg/m³
Worker DNEL, long-term		inhalation	local	5,58 mg/m³
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified			
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m³
Worker DNEL, long-term		inhalation	local	5,58 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,74 mg/kg bw/day
18760-44-6	Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich			
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	350 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	24,7 mg/m³
Consumer DNEL, long-term		inhalation	systemic	4,35 mg/m³

PNEC values

CAS No	Name of agent	
Environmental compartment	Value	
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil - unspecified	
Secondary poisoning	9,33 mg/kg	

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. EN 166

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Replace when worn.

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 6 of 11

Suitable material:

Preventive skin protection by protective skin ointment.

Skin protection

The type of personal protective equipment must be selected depending on the concentration and quantity of the hazardous substance at the workplace. For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Chemical resistant safety shoes

Respiratory protection

Generation/formation of mist: Filtering device with filter or ventilator filtering device of type:A2 P2

Environmental exposure controls

Technical measures for preventing exposition

Organisational measures for preventing exposition

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	red
Odour:	characteristic

		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	>320 °C	
Flammability:	not determined	
Lower explosion limits:	0,6 Vol.-%	
Upper explosion limits:	6,5 Vol.-%	
Flash point:	> 200 °C	DIN ISO 2592
Auto-ignition temperature:	not determined	
Decomposition temperature:	not applicable	
pH-Value::	not applicable	
Viscosity / kinematic: (at 40 °C)	28 mm ² /s	ASTM D7279
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 15 °C):	0,825-0,865 g/cm ³	DIN EN ISO 12185
Relative vapour density:	not determined	
Particle characteristics:	not applicable	

9.2. Other information

Information with regard to physical hazard classes

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 7 of 11

Explosive properties

No data available

Other safety characteristics

Pour point:

<-48 °C ASTM D7346

Further Information

none

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The formation of combustible vapours is possible at temperatures above: Flash point

10.4. Conditions to avoid

Oxidising agent, strong

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Refer to section 5.3.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Angaben zu den Gefahrenklassen im Sinne der Verordnung (EG) Nr. 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Frequently or prolonged contact with skin may cause dermal irritation.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 8 of 11

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Further information

There are no data available on the mixture itself.

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

Reference to other sections: 2, 3

SECTION 12: ECOLOGICAL INFORMATION**12.1. Toxicity**

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Pimephales promelas	OECD 203	
	Acute fish toxicity	ErC50 >100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 >10000 mg/l	48 h	Daphnia magna	OECD 202	
	Fish toxicity	NOEC >1000 mg/l	14 d	Oncorhynchus mykiss	QSAR	
	Crustacea toxicity	NOEC 10 mg/l	12 d	Daphnia magna	OECD 211	

12.2. Persistence and degradability

There are no data available on the mixture itself.

Not readily biodegradable (according to OECD criteria). Data apply to the main component.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 9 of 11

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow uncontrolled discharge of product into the environment.

Further information

There are no data available on the mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal recommendations

The allocation of waste code numbers/ descriptions shall be carried out in accordance with the List of Wastes Resolution 2000/532/EC on an industry- and process-specific basis.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Packaging containing oil is classified as packaging of pollutant-containing products. They are therefore not subject to collection by nationwide packaging take-back systems.

Oil packaging that has been emptied down to the residues that usually remain in it is subject to take-back by manufacturers and distributors.

Recommendation for disposal: Contacting the supplier / contractual partner.

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 10 of 11

SECTION 14: TRANSPORT INFORMATION

Land transport (ADR/RID)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

SYNOX GEAR ATF DEX VI

Revision date: 04/01/2026

Product code: 21600

Page 11 of 11

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: OTHER INFORMATION**Changes**

This data sheet contains changes from the previous version in section(s): 2,8.

Abbreviations and acronyms

Asp. Tox: Aspiration hazard

Aquatic Chronic: Chronic aquatic hazard

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

EUH210 Safety data sheet available on request.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(Die Daten der relevanten Bestandteile wurden jeweils dem letztgültigen Sicherheitsdatenblatt des Vorlieferanten entnommen.)