

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 1 of 15

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

SYNOX GEAR ATF XT 9S

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricating agent

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	MIDCO Lubes GmbH
Street:	Bruchkampweg 23
Place:	D-29227 Celle
Telephone:	+49 5141 9880-20
E-Mail:	info@midco-lubes.com
Internet:	www.synox-oil.com

1.4. Emergency telephone number: Giftinformationszentrum Nord (Göttingen)
+49 (0)551/19240

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May be fatal if swallowed and enters airways.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified

Signal word: Danger**Pictograms:**

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 2 of 15

Hazard statements

- H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P273 Avoid release to the environment.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents / container in accordance with official regulations.

2.3. Other hazards

No information available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Chemical characterization**

Preparation of base oils and additives.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			27 - <= 45 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified			25 - <= 43 %
	276-737-9	649-482-00-X	01-2119474878-16	
	Asp. Tox. 1; H304			
36878-20-3	BIs(nonylphenyl)amine			0 - < 1,2 %
	253-249-4		01-2119488911-28	
	Aquatic Chronic 4; H413			
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			0 - < 1,2 %
	406-040-9	607-530-00-7	01-0000015551-76	
	Aquatic Chronic 4; H413			
	Reaction product of alkylthioalcohol and substituted phosphorus compound			0 - < 0,24 %
	424-820-7		01-0000017126-75	
	Acute Tox. 4, Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 1; H312 H314 H400 H410			
91-20-3	naphthalene			0 - < 0,0001 %
	202-049-5	601-052-00-2	01-2119561346-37	
	Carc. 2, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H351 H302 H400 H410			

Full text of H and EUH statements: see section 16.

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	27 - <= 45 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
72623-86-0	276-737-9	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified	25 - <= 43 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
36878-20-3	253-249-4	Bis(nonylphenyl)amine	0 - < 1,2 %
		oral: LD50 = > 5000 mg/kg	
125643-61-0	406-040-9	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	0 - < 1,2 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
	424-820-7	Reaction product of alkylthioalcohol and substituted phosphorus compound	0 - < 0,24 %
		dermal: LD50 = > 500 mg/kg; oral: LD50 = > 2000 mg/kg M akut; H400: M=10 M chron.; H410: M=10	
91-20-3	202-049-5	naphthalene	0 - < 0,0001 %
		inhalativ: LC50 = > 77,7 mg/l (Dämpfe); dermal: LD50 = > 16000 mg/kg; oral: LD50 = 710 mg/kg	

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. Call a doctor if you feel unwell.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Take off contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth thoroughly with water.

Let water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 4 of 15

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media****Suitable extinguishing media**

Use water spray jet to protect personnel and to cool endangered containers.

Co-ordinate fire-fighting measures to the fire surroundings.

- Water spray jet
- alcohol resistant foam.
- Carbon dioxide (CO₂).
- Extinguishing powder

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Nitrogen oxides (NO_x)
- Carbon monoxide (CO)
- Carbon dioxide (CO₂)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Use of protective clothing

In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Keep people at a distance and stay on the windward side.

Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear protective gloves/protective clothing and eye/face protection.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

Prevent spread over a wide area (e.g. by containment or oil barriers).

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 5 of 15

6.3. Methods and material for containment and cleaning up**For containment**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling****Advice on safe handling**

Avoid formation of oil dust.

Use personal protection equipment.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Clear spills immediately.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Take precautionary measures against static discharges .

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed.

Floors should be impervious, resistant to liquids and easy to clean.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

Note Regulation on facilities for the storage, filling and handling water-polluting substances.

7.3. Specific end use(s)

Lubricating agent

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	ibres/m ³	Category	Origin
91-20-3	Naphthalene	10	50		TWA (8 h)	EU

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL Typ	Exposure route		Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation		systemic	2,73 mg/m ³
Worker DNEL, long-term	inhalation		local	5,58 mg/m ³
Worker DNEL, long-term	dermal		systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation		local	1,19 mg/m ³
Consumer DNEL, long-term	oral		systemic	0,74 mg/kg bw/day
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified			
Worker DNEL, long-term	inhalation		systemic	2,73 mg/m ³
Worker DNEL, long-term	inhalation		local	5,58 mg/m ³
Worker DNEL, long-term	dermal		systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation		local	1,19 mg/m ³
Consumer DNEL, long-term	oral		systemic	0,74 mg/kg bw/day
36878-20-3	BIs(nonylphenyl)amine			
Worker DNEL, long-term	dermal		systemic	5 mg/kg bw/day
Consumer DNEL, long-term	dermal		systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term	oral		systemic	0,25 mg/kg bw/day
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			
Worker DNEL, long-term	dermal		systemic	1,67 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	1,62 mg/m ³
Consumer DNEL, long-term	dermal		systemic	0,83 mg/kg bw/day
Consumer DNEL, long-term	oral		systemic	0,93 mg/kg bw/day
Worker DNEL, long-term	inhalation		systemic	6,6 mg/m ³
	Reaction product of alkylthioalcohol and substituted phosphorus compound			
Worker DNEL, long-term	inhalation		systemic	1,76 mg/m ³
Worker DNEL, long-term	dermal		systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	0,43 mg/m ³
Consumer DNEL, long-term	dermal		systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term	oral		systemic	0,25 mg/kg bw/day
91-20-3	naphthalene			
Worker DNEL, long-term	inhalation		systemic	25 mg/m ³
Worker DNEL, long-term	inhalation		local	25 mg/m ³
Worker DNEL, long-term	dermal		systemic	3,57 mg/kg bw/day

PNEC-Werte

CAS No	Substance	
Environmental compartment	Value	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning	9,33 mg/kg	
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified	
Secondary poisoning	9,33 mg/kg	

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 7 of 15

36878-20-3	Bis(nonylphenyl)amine	
Freshwater		0,412 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,041 mg/l
Freshwater sediment		1 mg/kg
Marine sediment		0,1 mg/kg
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	
Freshwater		0,018 mg/l
Freshwater (intermittent releases)		0,018 mg/l
Marine water		0,002 mg/l
Freshwater sediment		2 mg/kg
Marine sediment		0,2 mg/kg
Secondary poisoning		41,33 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		10 mg/kg
	Reaction product of alkylthioalcohol and substituted phosphorus compound	
Freshwater		0,0009 mg/l
Freshwater (intermittent releases)		0,0009 mg/l
Marine water		0,00009 mg/l
Freshwater sediment		0,73 mg/kg
Marine sediment		0,073 mg/kg
Secondary poisoning		10 mg/kg
Micro-organisms in sewage treatment plants (STP)		5 mg/l
Soil		0,086 mg/kg
	naphthalene	
Freshwater		0,0024 mg/l
Freshwater (intermittent releases)		0,02 mg/l
Marine water		0,0024 mg/l
Freshwater sediment		0,0672 mg/kg
Marine sediment		0,0672 mg/kg
Micro-organisms in sewage treatment plants (STP)		2,9 mg/l
Soil		0,0533 mg/kg

8.2. Exposure controls



Protective and hygiene measures

Take off contaminated clothing and wash it before reuse.

Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

Eye/face protection

During filling, metering, mixing and sampling must be used:

Wear eye/face protection. DIN EN 166

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 8 of 15

Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Tested protective gloves must be worn. EN ISO 374

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respirative protection necessary.

In case of inadequate ventilation wear respiratory protection.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	yellow
Odour:	Mineral-oil-like
Odour threshold:	not determined

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Pour poin:	-54 °C
Flash point:	184 °C

Flammability

Solid/liquid:	not applicable
Gas:	not applicable

Explosive properties

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Lower explosion limits:	not determined
Upper explosion limits:	not determined

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

The product is not: oxidising.

Vapour pressure:	not determined
Density (at 15 °C):	0,842 g/cm ³

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 9 of 15

Solubility in other solvents

not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / kinematic: (at 40 °C)	18 mm ² /s
Relative vapour density:	not determined
Evaporation rate:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reaction with: Oxidizing agent

10.4. Conditions to avoid

Avoid: Thermal decomposition

10.5. Incompatible materials

Materials to avoid:

- Acids
- Reducing agent
- Oxidising agent

10.6. Hazardous decomposition products

Hazardous combustion products:

- Carbon monoxide (CO)
- Carbon dioxide (CO₂)
- Nitrogen oxides (NO_x)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 10 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
72623-86-0					
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
36878-20-3					
	oral	LD50 > 5000 mg/kg	Rat	Study report (1981)	OECD Guideline 401
125643-61-0					
	oral	LD50 > 2000 mg/kg	Rat	Study report (2005)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2000)	OECD Guideline 402
	oral	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 401
	dermal	LD50 > 500 mg/kg	Rabbit	Study report (1996)	OECD Guideline 402
91-20-3					
	oral	LD50 710 mg/kg	Mouse	FUND. APPL. TOXICOL 4: 406-419 (1984) (1)	OECD Guideline 401
	dermal	LD50 > 16000 mg/kg	Rat	Study report (1980)	OECD Guideline 402
	inhalativ (4 h) Dampf	LD50 > 77,7 mg/l	Rat	Study report (1985)	other: EPA TSCA

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

No information available.

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 11 of 15

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
36878-20-3	Bis(nonylphenyl)amine					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Danio rerio (zebrafish)	ECHA Dossier	
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2019)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate					
	Acute fish toxicity	LC50 > 0,001 mg/l	96 h	Oncorhynchus mykiss	Study report (2009)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 0 mg/l	72 h	Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EL50 110 mg/l	48 h	Daphnia magna	Study report (2000)	OECD Guideline 202
	Fish toxicity	NOEC 0,36 mg/l	33 d	Pimephales promelas	Study report (2009)	OECD Guideline 210
	Crustacea toxicity	NOEC 3,2 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211
	Acute bacteria toxicity	(> 1000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (2000)	OECD Guideline 209
	Reaction product of alkylthioalcohol and substituted phosphorus compound					
	Acute fish toxicity	LC50 1,5 mg/l	96 h			
	Acute algae toxicity	ErC50 0,31 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1996)	EU Method C.3
	Acute crustacea toxicity	EL50 0,09 mg/l	48 h	Daphnia magna	Study report (1996)	EU Method C.2
	Crustacea toxicity	NOEC 0,14 mg/l	21 d	Daphnia magna	Study report (2001)	OECD Guideline 211
	Acute bacteria toxicity	(> 50 mg/l)	3 h	Belebtschlamm	Study report (1996)	OECD Guideline 209
91-20-3	naphthalene					
	Acute fish toxicity	LC50 1,6 mg/l	96 h	Oncorhynchus mykiss	Arch. Environm. Contam. Toxicol. 11, 487	OECD Guideline 203

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 12 of 15

	Acute algae toxicity	ErC50 ca. 0,4 - ca. 0,5 mg/l	72 h	Skeletonema costatum	Mar Environ Res 11, 183- 200 (1984)	Aquatic toxi- city of water soluble fracti
	Acute crustacea toxicity	EC50 2,16 mg/l	48 h	Daphnia magna	Transactions of the Ameri- can Fisheries S	OECD Guide- line 202
	Fish toxicity	NOEC 0,37 mg/l	40 d	Oncorhynchus kisutch	Trans. Am. Fish. Soc. 110:430-436, 1981	Coho salmon fry were exposed for 40 days
	Crustacea toxicity	NOEC 0,59 mg/l	125 d	Daphnia pulex	Can. J. Fish. Aquat. Sci. 39: 830 - 834	During chronic studies in closed static

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
36878-20-3	BIs(nonylphenyl)amine	7,6
91-20-3	naphthalene	3,4

BCF

CAS No	Chemical name	BCF	Species	Source
36878-20-3	BIs(nonylphenyl)amine	1584,89	Cyprinus carpio	Study report (2000)
125643-61-0	reaction mass of isomers of: C7- 9-alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	38	Cyprinus carpio	Study report (2002)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested..

12.6. Endocrine disrupting properties

No information available..

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 13 of 15

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: TRANSPORT INFORMATION

Land transport (ADR/RID)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 14 of 15

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC): 0 % (0,001 g/l)

2004/42/EC (VOC): 0 % (0,001 g/l)

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: OTHER INFORMATION

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,13,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50%

SYNOX GEAR ATF XT 9S

Revision date: 04/01/2026

Product code: 21790

Page 15 of 15

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)